



GENERAL CAR INFO		DIMENSIONS/CAPACITIES		SPECIALTY SUPPLIERS AND PART NUMBERS			
Built date	1992	Length (strikers)	57'-5"	Truck type (000-499)	ASF Ridemaster	Vertical wear ring(000-499)	ASF 43164D
Car builder	Trinity Industries	Coupled length	60'-0 1/2"	Bolster pattern/AAR code	22407-C/B9A-PPTN-FX	Vertical wear ring(500-999)	ASF 43210B
AFE number	92-1120	Truck ctrs.	45'-9"	Side frame patt./AAR code	22409-A/F9A-10DN-UA	Coupler/Knuckle (000-499)	ASF SBE60DE/E50AE
AAR Mech. Des.	LO	Inside length	55'-3 9/16"	Truck spring group	7 D-5 (O), 7 D-5 (I), 2 D6A (II)	Coupler/Knuckle (500-999)	M&T SBE60DE/E50AE
AAR Car Code	C113	Inside width	10'-0 1/2"	Snubbing type	ASF Ridemaster	Follower	Uniserve Y44HTE
GST Code	C6	Width (top chords)	10'-5 13/16"	Snubber spring group	2 #5062 (O), 2 #5063 (I)	Yoke (000-499)	ASF Y40AE
Type unloading	Gravity	Extreme width	10'-7 5/16"	Column wear plate	ASF 98-1-10333	Yoke (500-999)	M&T Y40AE
Clearance plate	C	Extreme height	14'-10 9/32"	Truck type (500-999)	ASF Ridemaster	Drft sill/Striker	Buckeye 42-30AX
C.G. - Empty	61.1"	Volume	4750 cu. ft.	Bolster pattern/AAR code	22407-E/B9A-PPTN-FX	Cp. carr. wear plt.	Schaefer 3258D
C.G. - Full to eaves	94.7"	Gross rail load	286,000 lbs.	Side frame patt./AAR code	22442-A/F9A-10DN-UA	Uncoupling rod	Triax CU-27674
Min. curve-Coupled	250' R(23°)	Lightweight	64,500 lbs.	Truck spring group	7 D-5 (O), 7 D-5 (I), 2 D6A (II)	Draft Gear/Cushioning	Miner Crown SE
Min. curve-Uncoupled	150' R(39°)	Load limit @ 263K	198,500 lbs.	Snubbing type	ASF Ridemaster	Brake system	Body mounted
Braking ratio - Empty	23.90%	Load limit @ 286K	221,500 lbs.	Snubber spring group	2 #5062 (O), 2 #5063 (I)	Control valve (000-499)	NYAB DB60
Braking ratio - Loaded	10.00%	Pinion ctr.hgt (Loaded)		Column wear plate	ASF 98-1-10232	Control valve (500-999)	Wabco ABDX
Braking ratio - H.B.	13.80%	Cars 000-249	12 7/8"	Pedestal roof liners	Transdyne A-05048	Brake cylinder	NYAB 10" x 12" ABU
		Cars 250-999	10 13/16"	Wheels	Griffin CH36, Ltwt.	Empty load brake	Ellicon 6200-5
		Pinion offset (000-249)	21 3/8"	Roller bearing (000-499)	Brenco HM133400	Slack adjuster	Universal 2300-DJ
		Pinion offset (250-999)	17 13/16"	Roller bearing (500-999)	Timken NFL wHDL Seals	Brake beam	Buffalo BB-376 (#24)
		Outlet gate size	24" x 30"	Adapter	R.H. Little 6 1/2" x 12"	Brake beam wear elim.	Holland WE-5500
<b>FORMER ROAD NUMBERS</b>		Min. gate to rail (000-249)	9 1/8"	Truck side bearing	Stucki 688-BR	Brake shoes	Cobra 1 1/2" comp.
		Min. gate to rail (250-999)	8 13/16"	Horz. ctr plt liner(000-499)	Lyman LY590	Handbrake	Ellicon D-5600-2
		Trough opening	24" x 47'-8"	Horz. ctr plt liner(500-999)	Clifton CL-138R	Outlet gate(000-249)	Railcar Spcl. HG-243047B
				Outlet gate(250-999)	Miner MKE-8675	Hatch covers	Danco F-3005-1/F-3006-1
				Running boards	YSD 90-64617B		
<b>NOTES AND EXCEPTIONS:</b>							
Approved: 7/20/95; SCL; Rev. B 05/06/97							